



Art.Nr. **LNL325/3**



1m	553.1,18091x	286.91cm
2m	138.3,452.31x	573.81cm
3m	61.46,201.01x	860.72cm
4m	34.57,113.11x	1147.62cm
5m	22.12,72.371x	1434.53cm
6m	15.36,50.261x	1721.43cm
7m	11.29,36.921x	2008.34cm
8m	8.642,28.271x	2295.24cm
9m	6.829,22.341x	2582.15cm
10m	5.531,18.091x	2869.05cm

- 50W
- 6500Lm
- 4000K – neutral white
- IP65
- AC180 - 265V
- 120°
- Recommended ambient temperature -25° to +65°C
- Thermal PC-white
- Possibly to connect max. 1000W
- IK08
- E
- Dimension 1500 x 66 x 57 mm
- Weight netto – 1010g
- 50000h
- Warranty 5 years
- Non-dimmable
- Packing 1/25

<https://nedes.eu/led-connect-light-50w/ip65-lw/3/1500/2835/4000k-lnl325/3/p-358>

<https://nedes.eu>



Art.Nr. **LNL325/3**



1m	553.1,18091x	286.91cm
2m	138.3,452.31x	573.81cm
3m	61.46,201.01x	860.72cm
4m	34.57,113.11x	1147.62cm
5m	22.12,72.371x	1434.53cm
6m	15.36,50.261x	1721.43cm
7m	11.29,36.921x	2008.34cm
8m	8.642,28.271x	2295.24cm
9m	6.829,22.341x	2582.15cm
10m	5.531,18.091x	2869.05cm

- 50W
- 6500Lm
- 4000K – neutrálna biela
- IP65
- AC180 - 265V
- 120°
- Doporučená teplota okolia -25° až +65°C
- Thermal PC-biela
- Nadpáateľné do 1000W
- IK08
- E
- Rozmer 1500 x 66 x 57 mm
- Hmotnosť netto – 1010g
- 50000h
- Záruka 5 rokov
- Nestmievateľné
- Balenie 1/25

<https://nedes.sk/led-nadpaj.-svietidlo-50w/ip65-lw/3/1500/2835/4000k-lnl325/3/p358>



Art.Nr. **LNL325/3**



1m	553.1,18091x	286.91cm
2m	138.3,452.31x	573.81cm
3m	61.46,201.01x	860.72cm
4m	34.57,113.11x	1147.62cm
5m	22.12,72.371x	1434.53cm
6m	15.36,50.261x	1721.43cm
7m	11.29,36.921x	2008.34cm
8m	8.642,28.271x	2295.24cm
9m	6.829,22.341x	2582.15cm
10m	5.531,18.091x	2869.05cm

- 50W
- 6500Lm
- 4000K – neutrální bílá
- IP65
- AC180 - 265V
- 120°
- Doporučená teplota okolí -25° až +65°C
- Thermal PC-bílá
- Napojovatelné do 1000W
- IK08
- E
- Rozměr 1500 x 66 x 57 mm
- Hmotnost netto – 1010g
- 50000h
- Záruka 5 let
- Nestmívatelné
- Balení 1/25

<https://nedes.cz/led-prachotesne-svitidlo-50w/ip65-lw/3/1500/2835/4000k-lnl325/3/p-358>

<https://nedes.cz>



Art.Nr. **LNL325/3**



1m	553.1,18091x	286.91cm
2m	138.3,452.31x	573.81cm
3m	61.46,201.01x	860.72cm
4m	34.57,113.11x	1147.62cm
5m	22.12,72.371x	1434.53cm
6m	15.36,50.261x	1721.43cm
7m	11.29,36.921x	2008.34cm
8m	8.642,28.271x	2295.24cm
9m	6.829,22.341x	2582.15cm
10m	5.531,18.091x	2869.05cm

- 50W
- 6500Lm
- 4000K – természetes fehér
- IP65
- AC180 - 265V
- 120°
- Ajánlott környezeti hőmérséklet -25° és +65°C
- Thermal PC-fehér
- Sorolható max 1000W
- IK08
- E
- Méret 1500 x 66 x 57 mm
- Nettó tömeg - 1010g
- 50000h
- 5 év garancia
- Dimmelhető – nem
- Csomagolás 1/25

<https://nedes.hu/led-sorolhato-lampatest-50w/ip65-lw/3/1500/2835/4000k-lnl325/3/p-358>



Art.Nr. **LNL325/3**



1m	553.1,18091x	286.91cm
2m	138.3,452.31x	573.81cm
3m	61.46,201.01x	860.72cm
4m	34.57,113.11x	1147.62cm
5m	22.12,72.371x	1434.53cm
6m	15.36,50.261x	1721.43cm
7m	11.29,36.921x	2008.34cm
8m	8.642,28.271x	2295.24cm
9m	6.829,22.341x	2582.15cm
10m	5.531,18.091x	2869.05cm

- 50W
- 6500Lm
- 4000K – Neutralweiß
- IP65
- AC180 - 265V
- 120°
- Empfohlene Umgebungstemperatur -25° bis +65°C
- Thermal PC-Weiß
- Verbindung max. 1000W
- IK08
- E
- Dimension 1500 x 66 x 57 mm
- Nettogewicht – 1010g
- 50000St
- Garantiezeit 5 Jahre
- Nicht dimmbar
- Verpackung 1/25